

The Pro-Ag Bucket range have been expertly designed and manufactured using the latest technology ensuring all of our customers are supplied with the best attachments available. As part of our commitment to offer superior products, improvements have been made to provide a market leading range of quality buckets, offering a wide range of sizes/capacities to meet customer requirements.



- Improved Corner Fills and side stiffeners offering greater protection
- Rolled shell offering greater versatility for dump & roll back bias
- Boron 500 leading edge 200mm wide from BKT25range upwards
- Dome sides available as an optional extra
- Extra wear plates fitted to underneath of the bucket for strength
- Bolt on Wear Edge available as an optional extra
- Larger capacities available

Model	Capacity m3(ft3)	Height m(ft)	Depth m(ft)	Width m(ft)	Weight kg(lb)
BKT25-60	1.9(67)	1.22(4'0")	1.59(5'3")	1.83(6'0")	530(1166)
BKT25-66	2.1(74)	1.22(4'0")	1.59(5'3")	1.98(6'6")	555(1221)
BKT25-70	2.2(77)	1.22(4'0")	1.59(5'3")	2.13(7'0")	580(1276)
BK725-76	2.3(81)	1.22(4'0")	1.59(5'3")	2.29(7'6")	605(1331)
BKT25-80	2.5(88)	1.22(4'0")	1.59(5'3")	2.44(8'0")	630(1386)
BKT25-86	2.6(92)	1.22(4'0")	1.59(5'3")	2.59(8'6")	655(1441)
BKT27-60	2.0(71)	1.28(4'2")	1.68(5'6")	1.83(6'0")	590(1298)
BKT27-66	2.2(77)	1.28(4'2")	1.68(5'6")	1.98(6'6")	615(1353)
BKT27-70	2.5(85)	1.28(4'2")	1.68(5'6")	2.13(7'0")	640(1408)
BKT27-76	2.4(92)	1.28(4'2")	1.68(5'6")	2.29(7'6")	665(1463)
BKT27-80	2.7(95)	1.28(4'2")	1.68(5'6")	2.44(8'0")	690(1518)
BKT27-86	3.0(106)	1.28(4'2")	1.68(5'6")	2.59(8'6")	715(1573)
BKT30-70	2.7(95)	1.34(4'5")	1.74(5'9")	2.13(7'0")	680(1496)
BKT30-76	2.9(102)	1.34(4'5")	1.74(5'9")	2.29(7'6")	710(1562)
BKT30-80	3.0(106)	1.34(4'5")	1.74(5'9")	2.44(8'0")	740(1628)
BKT30-86	3.3(116)	1.34(4'5")	1.74(5'9")	2.59(8'6")	770(1694)

