

Strimech Shear Grab range based around 6 width sizes and designed to give optimum performance, efficiently with high strength and longevity. The Shear Master silage block cutter heavy duty is designed to cut grass and maize silage from a silage clamp efficiently and leave behind a smooth clamp face, while sharp the serrated blades are designed to leave a sealed pit face which eliminates secondary fermentation. The new design comes with 2 robust stops fitted, preventing the cutting blade from coming into contact with the ground. Essential components within the design being Hardox material providing maximum durability while hydraulic rams are also perfectly matched for the grab size and the 3 ram models having our smart hydraulics system offering protection to both attachment & machine giving unrivalled performance. An option for weld on & bolt on bracket for the machine pick up, the bolt-on option giving quick & simple change swapping over from machine to machine between current & new fleet or if the handler is changed.

- All cutting blades are Hardox.
- Boron 500 bucket toe plate.
- Heavy duty 10mm box section.
- All pivot points are fully bushed.
- Suitable for all types of feeds whole to precision crop including Maze and grains.
- Bolt on bracket system allowing a wide range of machine compatibility.
- Full spare parts back up.



Model	Capacity (m ³)	Overall Width (mm)	Cutting Width (mm)	Tine Qty	Knife Blade Qty	Hyd Rams	Weight (kg)
SG214	0.88	1400	1300	9	5	2	910
SG214X	0.88	1400	1300	9	5	2	933
SG216	1.03	1600	1500	10	6	2	946
SG216X	1.03	1600	1500	10	6	2	971
SG218	1.16	1800	1700	12	7	2	986
SG218X	1.16	1800	1700	12	7	2	1017
SG320	1.29	2000	1900	14	8	2	814
SG320X	1.29	2000	1900	14	8	2	849
SG222	1.43	2200	2100	15	9	2	1061
SG222X	1.43	2200	2100	15	9	2	1100
SG322	1.43	2200	2100	14	9	3	844
SG322X	1.43	2200	2100	14	9	3	879
SG224	1.57	2400	2300	16	10	2	1096
SG224X	1.57	2400	2300	16	10	2	1138
SG324	1.57	2400	2300	16	10	3	884
SG324X	1.57	2400	2300	16	10	3	925

