

Pro Ag Tractor Loader Grab being our entry level range, design for the small end of the carrier market while maintaining the Strimech strength and reliability. This range spans from 5ft – 7ft 6” and KV or Hardox tines are optional for all models.

- Wide opening grab
- Large main pivot pins with main pivot boss nylon bushed
- Heavy duty box section base for tine mounting
- Hydraulic rams strategically placed to prevent material build up
- Hardox tine option for all models



Model	Capacity (m <sup>3</sup> )	Height (mm)	Depth (mm)	Tines	Weight (kg)
TLG-50KV	0.85	820	820	4 x top 680mm/8 x base 820mm	350
TLG-50X	0.85	820	820	4 x top 680mm/8 x base 820mm	360
TLG-56KV	0.90	820	820	5 x top 680mm/8 x base 820mm	372
TLG-56X	0.90	820	820	5 x top 680mm/8 x base 820mm	380
TLG-60KV	0.95	820	820	5 x top 680mm/8 x base 820mm	395
TLG-60X	0.95	820	820	5 x top 680mm/8 x base 820mm	410
TLG-66KV	1.00	820	820	5 x top 680mm/8 x base 820mm	405
TLG-66X	1.00	820	820	5 x top 680mm/8 x base 820mm	420
TLG-70KV	1.05	820	820	5 x top 680mm/8 x base 820mm	425
TLG-70X	1.05	820	820	5 x top 680mm/8 x base 820mm	435
TLG-76KV	1.10	820	820	5 x top 680mm/8 x base 820mm	468
TLG-76X	1.10	820	820	5 x top 680mm/8 x base 820mm	480