

The general purpose KV Tine & The heavy duty Buckrake is fitted with Hardox tines as standard for intensive, high frequency use option Buckrake is suitable for a wide range of Tractors, Telescopic Handlers & Loading Shovels. The Buckrake can be operated on Tractors with a minimum 150BHP and as with the Hardox tine option is fitted as standard with three point linkage for machines with Cat 2/3 pick up systems.. The power and durability of the design make this an ideal option for Contracting work. The H/D Buckrake is designed for Tractors of 160+ BHP and for Telescopic Handlers/Loading Shovels with a lift capacity of 4000kg +.



- 1400 long Kvernel and Tines
- 1660 long Hardox tines
- 3 Point Linkage Cat 2/3
- Heavy duty push off gate gives good operator visibility
- Flow regulator compensating valve
- Telescopic Handlers/Loading Shovel Adaptor Brackets available as optional extra



Model	Capacity	Height	Depth	Width m/ft	Weight
BSD8KV	3.46m ³	1.65m	1.56m	2.44m/8ft	1235kg
BSD8HX	4m ³	1.65m	1.74m	2.44m/8ft	1360kg
BSD9KV	4.02m ³	1.65m	1.56m	2.74m/9ft	1308kg
BSD9HX	4.65m ³	1.65m	1.74m	2.74m/9ft	1440kg
BSD10KV	4.5m ³	1.65m	1.56m	3.05m/10ft	1350kg
BSD10HX	5.2m ³	1.65m	1.74m	3.05m/10ft	1500kg
BSD12X	6.36m ³	1.65m	1.74m	3.66m/12ft	1630kg

